

graboflex START




<i>Property</i>	<i>Standard</i>	<i>Unit</i>	<i>Result</i>
-----------------	-----------------	-------------	---------------

DESCRIPTION			
Top layer	-	-	PUR Surface
Backing	-	-	Closed cell PVC foam
Thickness	EN 428	mm	4
Weight	EN 430	kg/m ²	2,7
Width	EN 426	m	2
Standard roll length	EN 426	m	20 ± 10%
Maximal roll length	EN 426	m	25

CLASSIFICATION			
Product specification	EN 651 Vinyl floor covering for indoor sport purposes Meets the requirements of EN 14904 on sub-constructions		
Thermal resistance	-	m ² K/W	0,03
Reaction to fire	EN 13501	-	C _{fl} -s1
Formaldehyde emission	-	-	No formaldehyde
Pentachlorophenol	-	-	No pentachlorophenol

SPORT PROPERTIES			
Ball rebound	EN 12235	%	> 90
Specular gloss	EN 2813	%	< 30

TECHNICAL CHARACTERISTICS			
Dimensional stability	EN 434	%	± 0,2
Indentation resistance	EN 433	mm	0,35
Colour fastness	ISO 105 B02	-	6
Chemical resistance	EN 423	-	no change
Abrasion group	EN 660-1		T

OTHERS			
Limited warranty			5 years
Environmental attributes	 		No periodic renewal needed; Solvent and heavy metal free