

HOMOGENEOUS
COMPACT VINYL

Centra 43

CERTIFICATION & CLASSIFICATION		STANDARDS	Centra 43
Classification	ISO 10874 – EN 685		Commercial: 34 Industrial: 43
Type of floor covering	ISO 10581 – EN 649		Homogeneous vinyl flooring. Single layered. Type I.
ISO certification			Jaslo ISO 9001, Jaslo ISO 14001
TECHNICAL CHARACTERISTICS		STANDARDS	Centra 43
Total thickness	ISO 24346 – EN 428		2.0 mm
Wear layer thickness	ISO 24340 – EN 429		2.0 mm
Total weight/m²	ISO 23997 – EN 430		3000 g
PUR			Yes
TECHNICAL PERFORMANCES		STANDARDS	Centra 43
Residual indentation	ISO 24343-1 – EN 433		Requirement ≤ 0.1 mm
Reaction to fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2		Class B _{fl} s1 ≥ 8 kW/m ² Pass
Dimensional stability	ISO 23999 – EN 434		≤ 0.40 % for rolls ≤ 0.25 % for tiles
Castor chair test	ISO 4918 – EN 425		Suitable
Static electrical charge	EN 1815		≤ 2 kV
Electrical resistance	EN 1081		≤ 10 ⁹ Ω
Light fastness	EN ISO 105-B02		≥ level 6
Chemical resistance	ISO 26987 – EN 423		Good resistance
Bacteria resistance	ISO 846: Part C		Does not favour growth
Clean room test	ASTM F24-04 ASTM F51-00		Class A
Slip resistance	DIN 51130 EN 13893		R9 ≥ 0.3
Underfloor heating			Suitable – max 27°C
Form of delivery	ISO 24341 – EN 426 Sheet (rolls)		Approx. 20 running metres x 200 cm
	ISO 24342 – EN 427 Tiles (box)		61.0 x 61.0* cm – 14 tiles/box = 5.21 m ² 50.0 x 50.0* cm – 24 tiles/box = 6 m ²
Colours			18

* Available for orders for at least 700 m²

The above information is subject to modification for the benefit of further improvement (03/2015).