

HOMOGENEOUS
COMPACT VINYL

Norma 43

CERTIFICATION & CLASSIFICATION		STANDARDS	Norma 43
Classification		ISO 10874 – EN 685	Commercial: 34 Industrial: 43
Type of floorcovering		ISO 10581 – EN 649	Homogeneous vinyl flooring. Single layered. Type I.
ISO certification			Jaslo ISO 9001, Jaslo ISO 14001
TECHNICAL CHARACTERISTICS		STANDARDS	Norma 43
Total thickness		ISO 24346 – EN 428	2.0 mm
Wear layer thickness		ISO 24340 – EN 429	2.0 mm
Total weight/m²		ISO 23997 – EN 430	2700 g
PUR			Yes
TECHNICAL PERFORMANCES		STANDARDS	Norma 43
Residual indentation		ISO 24343-1 – EN 433	Requirement ≤ 0.1 mm
Reaction to fire		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class B _{fl} s1 ≥ 8 kW/m ² Pass
Dimensional stability		ISO 23999 – EN 434	≤ 0.40 % for rolls ≤ 0.25 % for tiles
Castor chair test		ISO 4918 – EN 425	Suitable
Static electrical charge		EN 1815	≤ 2 kV
Electrical resistance		EN 1081	≤ 10 ⁹ Ω
Light fastness		EN ISO 105-B02	≥ level 6
Chemical resistance		ISO 26987 – EN 423	Good resistance
Fungi and bacteria resistance		ISO 846: Part C	Does not favour growth
Clean room test		ASTM F24-04 ASTM F51-00	Class A
Slip resistance		DIN 51130 EN 13893	R9 ≥ 0.3
Underfloor heating			Suitable – max 27°C
Form of delivery		ISO 24341 – EN 426 Sheet (rolls)	Approx. 20 running meters x 200 cm
		ISO 24342 – EN 427 Tiles (box)	61.0 x 61.0*cm – 14 tiles/box = 5.21 m ² 50.0 x 50.0*cm – 24 tiles/box = 6 m ²
Colours			24

* Available for orders for at least 700 m²

The above information is subject to modification for the benefit of further improvement (03/2015).